INSPECTION DOCUMENT 05

Date:	
Registration Number:	
Serial Number:	
Total Time:	

1. Description

- A. Inspection Document 05 gives a list of item(s), which are completed at every 144 calendar months.
- B. Inspection items are given in the sequence of the zone in which the inspection is completed. A description of the inspection, as well as the Item Code Number are supplied for cross-reference to section 5-10-01. Frequently, tasks give more information about each inspection. These tasks are found in the individual chapters of this manual.
- C. The right portion of each page gives space for the mechanic's and inspector's initials and remarks. You can use copies of these pages as a checklist while you complete the tasks in this Inspection Document.

2. General Inspection Criteria

- A. As you complete each of the inspection tasks in this Inspection Document, examine the adjacent area while access is available to find conditions that need more maintenance.
- B. If it is necessary to replace a component or to make a change to a system while you complete a task, do the task again before the system or component is returned to service.
- C. Inspection Kits are available for some Inspection Documents. They supply consumable materials used to complete the inspection item(s) given for the interval. Refer to the Model 208 Illustrated Parts Catalog, Introduction, Service Kit List to find applicable part numbers.

ITEM CODE NUMBER	TASK	ZONE	МЕСН	IN- SP	REMARKS
B262003	Portable Fire Extinguisher Restoration (Hydrostatic Test) Task 26-20-00-780	215 216 251 252			
	*** End of Inspection Document 05 Inspection Items ***				

	Tael	k 26-20-00-780
4.		table Fire Extinguisher Restoration (Hydrostatic Test)
	ΝΟΤ	E: One hand operated portable fire extinguisher is mounted in the flight compartment on the pilot's door, or mounted between the pilot and the copilot seats on the cargo barrier.
	A.	 General (1) This task includes the steps necessary to do a restoration (hydrostatic test) of the portable fire extinguisher.
	В.	Special Tools (1) None
	C.	Access (1) None
	D.	 Do the Portable Fire Extinguisher Restoration (Hydrostatic Test). (1) Remove the hand fire extinguisher from the quick release, clamp type bracket assembly. (2) Send the portable fire extinguisher to an approved fire extinguisher service facility for the hydrostatic test. (3) Install the hand fire extinguisher in the quick release, clamp type bracket assembly.
	E.	Restore Access (1) None
	End	Task