OXYGEN MASKS - INSPECTION/CHECK

1. General

A. This section has the inspections and checks necessary to keep the oxygen masks in a serviceable condition. **TASK 35-15-00-960**

2. Oxygen Mask Restoration (Overhaul)

- A. General
 - (1) The crew masks are located on the crew doors. The passenger oxygen masks are located in different areas of the cabin depending on the seating configuration.
- B. Special Tools
 - (1) None
- C. Access
 - (1) None
- D. Do the Oxygen Mask Restoration (Overhaul). Refer to Table 601 for the correct Cessna and supplier part numbers.
 - NOTE: A restoration (overhaul) on the mask is done at six years from the date of the manufacture or six years from the date of the last overhaul.
 - (1) Remove the masks from the storage containers.
 - (2) Send the masks to an approved repair facility for an overhaul.
 - (3) Install the masks in the storage containers.

Table 601. Oxygen Mask Restoration (Overhaul)

Cessna Part Number	Supplier Name and Part Number	Restoration (Overhaul) Interval
C166015-0101	B/E Aerospace 174406-01	6 years
C166015-0101	Avox 802065-03	6 years
C166015-0102	B/E Aerospace 174441-01	6 years
359A3552	Avox 359A3552	6 years

E. Restore Access

(1) None END OF TASK

Copyright © Textron Aviation Inc. Retain printed data for historical reference only. For future maintenance, use only current data.